



**BOTTOM VIEW**

PROCESS		P & B								SPECIFICATION AGREEMENT ARE BASED ON TOLERANCED DIMENSIONS ONLY DO NOT SCALE DRAWING COPYRIGHT RESERVED. NOT TO BE COPIED IN WHOLE OR PART WITHOUT WRITTEN PERMISSION FROM H.N.G.& I. LTD.					
MINIMUM THROUGH BORE															
FILL POINT VERIFIED															
TILT ANGLE		17.5°	REV.	NO.	REV.	BY	REVISION			DATE	CHK	DRC	<b>EKAM GLOBAL PTY LTD</b>  <b>TITLE : 150 ML BAMBOO BOTTLE</b> <b>CUSTOMER : .</b> <b>DRN : PRASHANT S.</b> <b>DR. DT. : 28/12/2014</b> <b>CHK.: KS1</b> <b>CHK. DT.</b> <b>APPD.</b> <b>APPD. DT.</b>		
MAXIMUM DEPTH OF STANDARD ENGRAVING		0.4	FILL-POINT		--- ± ---										
MAX. GAS VOLUMES		—	BRIMFUL CAP.		155 ± 6 ml										
REF DRG No : W1-01926-B			WEIGHT		175 ± 10 gms										
MOULD EQUIPMENT ORDERED BY			FINISH		53 mm LUG FINISH WITH RING			COLOUR	FLINT						
PLANT	SINNAR				SURFACE TREATMENT			-			C.C. NO.: HNG-00897	<b>DRAWING No.:</b>  <div style="text-align: center; font-size: 1.2em;"><b>HNG-00897</b></div>	<b>A3</b> <b>REV.</b>		