



<b>PROCESS</b>		<b>PRESS &amp; BLOW</b>								SPECIFICATION AGREEMENT ARE BASED ON TOLERANCED DIMENSIONS ONLY DO NOT SCALE DRAWING COPYRIGHT RESERVED. NOT TO BE COPIED IN WHOLE OR PART WITHOUT WRITTEN PERMISSION FROM EKAM GLOBAL PTY LTD			
<b>MINIMUM THROUGH BORE</b>		ø—								<b>EKAM GLOBAL PTY LTD</b>			
<b>FILL POINT VERIFIED</b>		-											
<b>TILT ANGLE</b>		—		<b>No.</b>	<b>REV.No.</b>	<b>REVISION</b>		<b>DATE</b>	<b>CHK</b>				
<b>MAXIMUM DEPTH OF STANDARD ENGRAVING</b>		—		<b>FILL-POINT</b>		-				<b>TITLE</b> 300 ML			
<b>MAX. GAS VOLUMES</b>		—		<b>BRIMFUL CAP.</b>		<b>300 ±10-ML.</b>				<b>CUST</b>			
<b>REF DRG No :- EKM/201/898</b>				<b>WEIGHT</b>		<b>205 ± 15 GMS.</b>				<b>DRN</b> TANMOY ROY		<b>DR. DT.</b> 26/01/2012	
										<b>CHK.</b> S BANERJEE		<b>CHK. DT.</b> 26/01/2012	
										<b>APPD.</b> -		<b>APPD. DT.</b> -	
<b>MOULD EQUIPMENT ORDERED BY</b>				<b>FINISH</b>		<b>63 LUG CAP</b>		<b>COLOUR</b>		<b>FLINT</b>		<b>DRAWING No. EKM-00353</b>	
<b>PLANT</b>				<b>R</b>									
				<b>SURFACE TREATMENT</b>		<b>NO</b>		<b>C.C. NO</b>		<b>-</b>		<b>A4 REV.</b>	